



# LERNER AND GREENBERG, P.A.

PATENT ATTORNEYS AND ATTORNEYS AT LAW

2200 Hollywood Boulevard  
Hollywood, Florida 33020  
Tel: (954) 925-1100  
Fax: (954) 925-1101

e-mail:  
patents@patentusa.com

Mailing Address:  
Post Office Box 2480  
Hollywood, FL 33022-2480

New York Office  
153 E 57th Street  
Suite 15G  
New York, NY 10022

Herbert L. Lerner (NY Bar)  
Laurence A. Greenberg (FL Bar)

Werner H. Stemer (Reg. Pat. Agent)  
Ralph E. Locher (FL, IL, MO Bars)  
Manfred Beck (German Pat. Agent only)  
Mark P. Weichselbaum (TN Bar)  
Gregory L. Mayback (FL Bar)  
Otto S. Kauder (Reg. Pat. Agent)  
Adam A. Jorgensen (Reg. Pat. Agent)



"Express Mail" mailing label number EL080657663US  
Date of Deposit May 28, 1999

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Docket No.: GR 98 P 4106

XIOMARA D. JUNCO

Date: May 28, 1999

Hon. Commissioner of Patents and Trademarks  
Washington, D.C. 20231

Sir:

Enclosed herewith are the necessary papers for filing the following application for Letters Patent:

Applicant : PETER HILDEBRANDT ET AL.

Title : COUPLING DEVICE

1 sheet of formal drawings in triplicate.

A check in the amount of \$760.00 covering the filing fee.

Information Disclosure Statement and 2 References.

This application is being filed without a signed oath or declaration under the provisions of 37 CFR 1.53(d). Applicants await notification of the date by which the oath or declaration and the surcharge are due, pursuant to this rule.

The Patent and Trademark Office is hereby given authority to charge Deposit Account No. 12-1099 of Lerner and Greenberg, P.A. for any fees due or deficiencies of payments made for any purpose during the pendency of the above-identified application.

Respectfully submitted,

For Applicants

LAURENCE A. GREENBERG  
REG. NO. 29,308

LAG:tg



EP 98 P 4106

COUPLING DEVICE

5 Background of the Invention:

Field of the Invention:

The invention lies in the field of optical connector technology, in particular releasable multichannel optical connections using plug-in connectors.

10

The invention pertains to a coupling device with an optical fiber holder which has a top face and a bottom face with narrow side faces between them, and with a receptacle into which the holder is inserted in a longitudinal direction.

15

A coupling device of this kind is known from a publication by H. Kosaga et al. entitled "Plastic-Based Receptacle-Type VCSEL-Array Modules with One and Two Dimensions Fabricated Using the Self-Alignment Mounting Technique," in ETC

20

Proceedings 1997 (Electronic Components and Technology Conference), p. 383-384. That device involves a holder designed as a plug-in connector for accepting several parallel optical fiber ends and with projecting aligning pins at the end face. Such holders are also designated as MT

25

ferrules. For its part the holder is brought into a plug-in connector housing with locking elements and is supported

floating therein. The holder has a top face, a bottom face and narrow side faces running rectangularly between these. The holder therefore has an essentially cuboidal geometry.

- 5 In the longitudinal direction (plug-in direction) the holder together with the plug-in connector housing can be inserted into a receptacle, also known as adapter or socket, whereby locking hooks of the receptacle engage with the locking elements of the plug-in connector housing. In the plugged-in state the aligning pins together with corresponding aligning bores enable the holder to be aligned in a laser module, or coupling partner to which it must be coupled, in such a way that the individual optical fiber ends taken up by the holder are aligned on optically active light-irradiating zones of a vertically emitting laser array within the module.
- 10
- 15

This is only possible, however, if it can be guaranteed that during the plug-in procedure the holder is successfully aligned with respect to the engagement of the aligning pins with the corresponding aligning bores. This in turn requires extremely precise fabrication, especially of the holder, on the one hand, and on the other, with respect to the positioning of the receptacle (adapter) relative to the module and the optically active zones. This is especially problematic in view of the trend towards ever increasing numbers of optical fibers in a common holder. Furthermore,

20

25

constructions of prior art from connection techniques used for mutual alignment of the coupling partners in single optical fiber connectors appear to be unsuitable on grounds of the flat structure of the holder.

5

Since the prior art device is subject to positioning tolerances both between the holder and the receptacle (adapter) and between the receptacle and the coupling partner (for example the electro-optical module), the prior art device demands the highest precision with respect to the fabrication of the individual components, of the assembly and of the positioning.

10

Summary of the Invention:

15

It is accordingly an object of the invention to provide an optical coupling device, which overcomes the above-mentioned disadvantages of the heretofore-known devices and methods of this general type and in which the optical fiber holder is reproducibly fixed free of play and accurately placed with respect to being taken up into a predefined relative position.

20

With the foregoing and other objects in view there is provided, in accordance with the invention, a coupling device, comprising:

25

an optical fiber holder having a top face, a bottom face,  
narrow side faces between the top face and the bottom face,  
with transition regions formed between the narrow side faces,  
and the top face and the bottom face, respectively, and

5 intermediate faces formed in the transition areas; and

a receptacle for receiving the holder along a longitudinal  
insertion direction, the receptacle having inside contact  
areas contacting the intermediate faces without play.

10 A considerable advantage of the invention is that the  
intermediate faces of the holder and the contact areas of the  
receptacle form corresponding alignment contours so that a  
precise, predeterminable relative positioning of holder and  
receptacle is guaranteed without further adjustment. This  
15 also leads to the considerable fabrication advantage that  
there is no need for a relative adjustment between holder and  
receptacle or for any subsequent mutual fixing by means of  
fixing material or other aids. A further advantage of the  
device according to the invention is that the support of the  
20 holder in the receptacle also allows a coupling partner  
intended to be coupled (for example a plug-in connector) to  
be fixed free from play. The fact that there is no play in  
the fixing means that tension and shearing forces on the  
coupling partner can be better diverted, which leads to a  
25 greater mechanical stability of the holder.

In accordance with an added feature of the invention, the holder has a substantially cuboid shape, and the intermediate faces are bevels formed along longitudinal edges defined by  
5 the cuboid shape.

In principle, the necessary force to be exerted on the contact areas or pressings for ensuring there is no play between the holder and the receptacle can be generated  
10 through flexible, plastic or elastoplastic resilient structures forming part of the receptacle. In this context, a preferred structural and fabrication-related embodiment of the invention involves the contact areas being part of a longitudinally aligned V-shaped recess.

15 In accordance with an additional feature of the invention, the contact areas are defined by a longitudinal V-shaped recess.

20 In accordance with a preferred embodiment, there are provided one or more rails in the receptacle, the rails having two resiliently splayable limbs forming the V-shaped recess.

In accordance with another feature of the invention, the V-  
25 shaped recess is formed between two limbs, and the contact

surface is formed from an at least partially plastically deformed section of the limb.

In other words, depending on the particular application and the combination of materials it may be advantageous for the V-shaped recess to be formed between two limbs of a rail, which limbs can splay resiliently apart. In accordance with a preferred embodiment of the invention, an at least partially plastic deformation of areas of the receptacle provided for that purpose is realized in that the V-shaped recess is formed between two limbs, whereby the contact area is formed from an at least partially plastically deformed section of the limb.

A preferred use of the invention involves the realization of coupling units or coupling sockets for multichannel electro-optical modules. In this respect it is advantageous if the receptacle is part of a coupling socket in one open side of which it is possible to insert an optical fiber plug-in connector which is to be coupled.

Other features which are considered as characteristic for the invention are set forth in the appended claims.

Although the invention is illustrated and described herein as embodied in coupling device, it is nevertheless not intended

to be limited to the details shown, since various modifications and structural changes may be made therein without departing from the spirit of the invention and within the scope and range of equivalents of the claims.

5

The construction and method of operation of the invention, however, together with additional objects and advantages thereof will be best understood from the following description of specific embodiments when read in connection with the accompanying drawing.

10

Brief Description of the Drawing:

Fig. 1 is a perspective view of a coupling device in accordance with the invention; and

15

Fig. 2 is a front elevational view of the fixing of a holder in a receptacle.

Description of the Preferred Embodiments:

20 Referring now to the figures of the drawing in detail and first, particularly, to Fig. 1 thereof, there is seen a greatly enlarged illustration of a coupling device in accordance with the invention. The coupling device includes an optical fiber holder 1. Solely for reasons of clearer  
25 representation, the holder 1 is shown separated from a receptacle 2, which is a part of a coupling socket 3. The



coupling socket 3 has a rearward end 3a which is provided for mechanical fixing to a non-illustrated electro-optical transmit/receive module (transceiver module), and is formed with a mounting flange 4. An opening 5 at the front-side end 5 3b of the coupling socket 3 is shaped for insertion of an additional optical fiber holder, which can essentially conform with the illustrated holder 1 and which can form a coupling partner for the holder 1. Lateral openings 7,8 of the coupling socket serve for engagement of corresponding 10 locating hooks of the coupling partner in a manner known, for example, from the publication mentioned at the beginning.

The holder 1 has a top face 1a and a bottom face 1b and as indicated in the drawing contains several, for example 15 twelve, optical fiber ends 10 running lengthwise parallel to one another (in the longitudinal direction L) between the front end-face and the rear end-face of the holder 1. Narrow-side faces 1c and 1d run between the a top face 1a and the bottom face 1b. The narrow-side faces 1c, 1d abut the 20 respective upper intermediate areas 1e and lower intermediate areas 1f which in turn abut respectively on the top face 1a and the bottom face 1b. The intermediate areas 1e, 1f are preferably formed such that the original cuboidal shaped body of the holder 1 is provided in each case with a bevel 14 25 through removal of the respective longitudinal edge 12. The original longitudinal edges and the areas of material removed

from the holder 1 in producing the bevels are indicated in Fig. 1 with broken lines. As a result a sloping intermediate face 1g, 1h runs respectively between each of the narrow-side faces 1c, 1d and the adjacent top face 1a and a sloping intermediate face 1i, 1k runs respectively between each of the narrow-side faces 1c, 1d and the adjacent bottom face 1b. It will be understood that the intermediate faces do not have to be identical to the exemplary embodiment of Fig. 1 but can also, for example, have a slightly concave shape. The essential issue involved in specifying the dimensions of the outside contour of the holder and the shape of the intermediate faces is to guarantee the interaction described below between the intermediate faces and the contact areas of the receptacle 2.

Referring now to Fig. 2, it is clear from the view into the rearward end 3a of the coupling socket 3 that the receptacle 2 has rails 20, 21 opposite one another on the inner longitudinal walls. The rails can also preferably be formed with a longitudinally running slot 22, 23. As a result the rails have limbs 20a, 20b and 21a, 21b, between which a recess 24, 25 with V-shaped cross-section exists.

In the mounted position the holder 1 is introduced into the receptacle 2 in the longitudinal direction L such that physical contact exists respectively between the intermediate

faces 1g to 1k and the corresponding facing contact areas 20c, 20d and 21c, 21d of the rails 20a, 20b and 21a, 21b. In a preferred embodiment the limbs can be flexibly splayed out through the holder 1 such that the V-shaped recesses 24, 25 are widened with resilient bending of the limbs. The resilient splaying of the limbs results in a reliable pressing-down force for generating an adequate physical contact between the contact area, say, 20c and the corresponding intermediate face 1g. The contact areas (e.g. 20c) can be fitted with protruding pinching ribs (not explicitly illustrated in the figure), which are flexibly deformed when the holder 1 is inserted into the receptacle 2 and thus provide for particularly effective physical contact.

The holder 1 may be formed with through bores 30, 31, which extend to its coupling-side end face 32 (Fig. 1) and accept centering pins or combine with centering pins of a coupling partner to provide precise alignment. Preferred is the coupling partner embodied as plug-in connector with an optical fiber holder, which is embodied correspondingly to the holder illustrated and thereby also benefits from the high-precision centering mechanism between its intermediate faces and the contact areas of the receptacle. The contact areas are preferably formed symmetrically to the level of the optical fiber ends 10.

We claim:

1. Coupling device, comprising:

an optical fiber holder having a top face, a bottom face, narrow side faces between said top face and said bottom face, with transition regions formed between said narrow side faces, and said top face and said bottom face, respectively, and intermediate faces formed in said transition areas; and a receptacle for receiving said holder along a longitudinal insertion direction, said receptacle having inside contact areas contacting said intermediate faces without play.

2. The coupling device according to claim 1, wherein said holder has a substantially cuboid shape, and said intermediate faces are bevels formed along longitudinal edges defined by the cuboid shape.

3. The coupling device according to claim 1, wherein said contact areas are defined by a longitudinal V-shaped recess.

4. The coupling device according to claim 3, which comprises two rails disposed in said receptacle, said rails each having two resiliently splayable limbs forming said V-shaped recess.

5. The coupling device according to claim 3, which comprises a rail disposed in said receptacle, said rail having two resiliently splayable limbs forming said V-shaped recess.

6. The coupling device according to claim 3, wherein said V-shaped recess is formed between two limbs, and said contact surface is formed from an at least partially plastically deformed section of said limb.

7. The coupling device according to claim 1, wherein said holder is a coupling unit of one of a multichannel transmitter module and receiver module.

8. The coupling device according to claim 1, wherein said holder is a coupling unit of a multichannel ~~transceiver~~ module.

9. The coupling device according to claim 1, wherein said receptacle forms a part of a coupling socket having an open side adapted to receive therein an optical fiber plug-in connector.

Abstract of the Disclosure:

The optical fiber holder of the coupling device has a top, a bottom, and narrow side faces between the top and the bottom. Intermediate faces are formed at the transitions between the narrow side faces and the top and the bottom. A receptacle into which the holder is inserted axially has internal contact areas which are in contact with the intermediate faces without play.

WHS:cj - 98P4106F//5/27/99




Fig 1




Fig 2

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; that I verily believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

described and claimed in the specification bearing that title, that I understand the content of the specification, that I do not know and do not believe the same was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve month prior to this application, that I acknowledge my duty to disclose information of which I am aware which is material to the examination of this application under 37 C.F.R. 1.56a, and that no application for patent or inventor's certificate of this invention has been filed earlier than the following in any country foreign to the United States prior to this application by me or my legal representatives or assigns:

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Address all correspondence and telephone calls to:

**LERNER AND GREENBERG, P.A.**  
**POST OFFICE BOX 2480**  
**HOLLYWOOD, FLORIDA 33022-2480**  
 Tel: (954) 925-1100  
 Fax: (954) 925-1101



I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF FIRST JOINT INVENTOR: PETER HILDEBRANDT

INVENTOR'S SIGNATURE: \_\_\_\_\_

DATE: \_\_\_\_\_

Residence: BERLIN, GERMANY

Country of Citizenship: GERMANY

Post Office Address: AM BERGHANG 6  
D-14089 BERLIN  
GERMANY

FULL NAME OF SECOND JOINT INVENTOR: LUTZ MELCHIOR

INVENTOR'S SIGNATURE: \_\_\_\_\_

DATE: \_\_\_\_\_

Residence: BERLIN, GERMANY

Country of Citizenship: GERMANY

Post Office Address: PHILIPP-RAUCH-STRASSE 56  
D-12559 BERLIN  
GERMANY